| Ref<br>#   | Hits | Search Query  | DBs   | Default<br>Operator | Plurals | Time Stamp       |
|------------|------|---|---|---------------------|---------|------------------|
| <b>S</b> 1 | 130  | (464/23).CCLS.  | USPAT   | OR                  | OFF     | 2005/07/07 13:34 |
| S2         | 226  | (464/23).CCLS.  | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR                  | OFF     | 2005/07/07 13:35 |
| S3         | 137  | (464/23).CCLS.  | US-PGPUB;<br>USPAT;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB           | OR                  | OFF     | 2005/07/07 13:35 |
| S4         | 0    | ("2004/0097289").URPN.  | USPAT   | OR                  | OFF     | 2005/07/07 13:35 |
| S5         | 4    | ("5657545").URPN.   | USPAT   | OR                  | OFF     | 2005/07/07 13:50 |
| S6         | 0    | an indicator plate disposed on an outer edge of the other of coupling parts, wherein marking and serve for a determination of a relative angle of torque of said first and second coupling parts, wherein said marking and said indicator plate are disposed on said coupling parts such that they are centered relative to one another, and wherein said marking and said indicator plate abut said coupling "gap."  an indicator plate disposed on an outer edge of the other of coupling | USPAT   | WITH                | OFF     | 2005/07/07 13:51 |
|            |      | parts, wherein marking and serve for a determination of a relative angle of torque of said first and second coupling parts, wherein said marking and said indicator plate are disposed on said coupling parts such that they are centered relative to one another, and wherein said marking and said indicator plate abut said coupling gap   | LICOAT  | W.T.                | OFF     |                  |
| S8         | 0    | indicator plate coupling marking<br>determination relative angle torque   | USPAT   | WITH                | OFF     | 2005/07/07 13:52 |
| S9         | 0    | indicator plate coupling marking determination relative angle torque  | USPAT   | SAME                | OFF     | 2005/07/07 13:52 |
| S10        | 0    | coupling marking determination relative angle torque  | USPAT   | SAME                | OFF.    | 2005/07/07 13:53 |
| S11        | 0    | coupl\$4 marking determination relative angle torque  | USPAT   | SAME                | OFF     | 2005/07/07 13:53 |
| S12        | 0    | coupl\$4 mark4\$ determination relative angle torque  | USPAT   | SAME                | OFF     | 2005/07/07 13:53 |

|     |      |   | ·                            |      |      |                  |
|-----|------|---|------------------------------|------|------|------------------|
| S13 | 0    | coupl\$4 mark4\$ determin\$5 angle torque   | USPAT                        | SAME | OFF  | 2005/07/07 13:53 |
| S14 | 3075 | coupl\$4 angle torque   | USPAT                        | SAME | OFF  | 2005/07/07 13:54 |
| S15 | 806  | coupl\$4 angle torque   | USPAT                        | WITH | OFF  | 2005/07/07 13:54 |
| S16 | 1    | coupl\$4 angle torque   | USPAT                        | NEAR | OFF  | 2005/07/07 13:54 |
| S17 | 3358 | torque adj sensor   | USPAT                        | NEAR | OFF  | 2005/07/07 13:55 |
| S18 | 3    | (torque adj sensor) and claw adj<br>coupling  | USPAT                        | NEAR | OFF  | 2005/07/07 13:59 |
| S19 | 6    | ("4712433"   "4805463"  <br>"4864873"   "4881414"   "5009110"<br>  "5020616").PN.   | US-PGPUB;<br>USPAT;<br>USOCR | OR   | OFF  | 2005/07/07 13:57 |
| S20 | 11   | (torque adj sensor) and (elast\$6<br>near coupling)   | USPAT                        | NEAR | OFF. | 2005/07/07 14:01 |
| S21 | 0    | (torque adj sensor) and (elast\$6 same strobe)  | USPAT                        | NEAR | OFF  | 2005/07/07 14:02 |
| S22 | 16   | (torque adj sensor) and (strobe)  | USPAT                        | NEAR | OFF  | 2005/07/07 14:04 |
| S23 | 637  | (position adj sensor) and (strobe)  | USPAT                        | NEAR | OFF  | 2005/07/07 14:04 |
| S24 | 0    | (position adj sensor) and (strobe) and claw adj coupling  | USPAT                        | NEAR | OFF  | 2005/07/07 14:05 |
| S25 | 0    | (position adj sensor) and (strobe) and claw near coupling   | USPAT                        | NEAR | OFF  | 2005/07/07 14:05 |
| S26 | 0    | (position adj sensor) and (strobe) and elast\$6 near coupling   | USPAT                        | NEAR | OFF  | 2005/07/07 14:05 |
| S27 | 53   | (position adj sensor) and (strobe) and elast\$6 and coupling  | USPAT                        | NEAR | OFF  | 2005/07/07 14:07 |
| S28 | 4    | (position near torque) and (strobe) and elast\$6 and coupling   | USPAT                        | NEAR | OFF  | 2005/07/07 14:13 |
| S29 | 34   | ("3495452"   "3564009"   "3885420"   "3934459"   "3950569"   "4102734"   "4121272"   "4148222"   "4235958"   "4317371"   "4430566"   "4433585"   "4464935"   "4482584"   "4551017"   "4578290"   "4621256"   "4641027"   "4727014"   "4783998"   "4806454"   "4818661"   "4844947"   "4885231"   "4975569"   "4978954"   "4995257"   "4997747"   "5001937"   "5328727"   "5365787"   "5438882").PN. | US-PGPUB;<br>USPAT;<br>USOCR | OR   | OFF  | 2005/07/07 14:09 |
| S30 | 1    | ("6257075").URPN.   | USPAT                        | OR   | OFF  | 2005/07/07 14:12 |
| S31 | 0    | (position near torque) and (strobe) and flex\$4 near coupling   | USPAT                        | NEAR | OFF  | 2005/07/07 14:13 |
| S32 | 27   | (position near torque) and flex\$4 near coupling  | USPAT                        | NEAR | OFF  | 2005/07/07 14:18 |

| S33 | 20 | ((position with torque) and (flex\$4 with coupling)) same indicator   | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT | NEAR | OFF | 2005/07/07 14:36  |
|-----|----|---|---|------|-----|-------------------|
| S34 | .5 | ("4102052").URPN.   | USPAT   | OR   | OFF | -2005/07/07 14:20 |
| S35 | 12 | ("0697701"   "1323046"  <br>"2516854"   "3163037"   "3688570"<br>  "3762217"   "3828562"  <br>"3871215").PN.  | US-PGPUB;<br>USPAT;<br>USOCR                          | OR   | OFF | 2005/07/07 14:21  |
| S36 | 2  | ("2432900").PN.   | US-PGPUB;<br>USPAT;<br>USOCR                          | OR   | OFF | 2005/07/07 14:26  |
| S37 | 9  | ("5009110").URPN.   | USPAT   | OR   | OFF | 2005/07/07 14:26  |
| S38 | 12 | ("0697701"   "1323046"  <br>"2516854"   "3163037"   "3688570"<br>  "3762217"   "3828562"  <br>"3871215").PN.  | US-PGPUB;<br>USPAT;<br>USOCR                          | OR   | OFF | 2005/07/07 14:28  |
| S39 | 5  | ("4102052").URPN.   | USPAT   | OR   | OFF | 2005/07/07 14:28  |
| S40 | 5  | ("4033042"   "4102052"  <br>"4428126"   "4516328"  <br>"4586264").PN.   | US-PGPUB;<br>USPAT;<br>USOCR                          | OR   | OFF | 2005/07/07 14:29  |
| S41 | 6  | ("5009110"   "5501110"  <br>"5731529"   "6227060"   "6269702"<br>  "6427542").PN.   | US-PGPUB;<br>USPAT;<br>USOCR                          | OR   | OFF | 2005/07/07 14:30  |
| S42 | 7  | ("5731529").URPN.   | USPAT   | OR   | OFF | 2005/07/07 14:31  |
| S43 | 5  | ("5195382"   "5394760"  <br>"5450761"   "5490431"  <br>"5501110").PN.   | US-PGPUB;<br>USPAT;<br>USOCR                          | OR   | OFF | 2005/07/07 14:31  |
| S44 | 14 | ("3111028"   "3170323"  <br>"3307164"   "3742243"   "3823607"<br>  "4173265"   "4430566"  <br>"4448084"   "4646088"   "4724710"<br>  "4851771").PN. | US-PGPUB;<br>USPAT;<br>USOCR                          | OR   | OFF | 2005/07/07 14:33  |
| S45 | 13 | ("5195382").URPN.   | USPAT   | OR   | OFF | 2005/07/07 14:34  |
| S46 | 0  | ((position with torque) near indicator and (flex\$4 same coupling))   | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT | NEAR | OFF | 2005/07/07 14:37  |
| S47 | 0  | ((position same torque) near indicator and (flex\$4 same coupling))   | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT | NEAR | OFF | 2005/07/07 14:37  |

| S48 | 2  | ((position and torque) near indicator and (flex\$4 same coupling)) | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT | NEAR | OFF | 2005/07/07 14:40 |
|-----|----|--|---|------|-----|------------------|
| S49 | 4  | ("2978901").URPN.  | USPAT   | OR   | OFF | 2005/07/07 14:38 |
| S50 | 46 | ((position and torque) with indicator and (flex\$4 same coupling)) | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT | NEAR | OFF | 2005/07/07 14:40 |